

TurfPickup TP600

Handy decompacting device for the loosening of infilled artificial turf

Hardened artificial turf pitches with sand and/or rubber granulate infill can be loosened by the TurfPickup TP600. The maneuverable TP600 is ideal especially for small facilities e.g. tennis courts or repair areas in larger facilities.

A rotating tine shaft loosens hardenings carefully and removes the infill material from the artificial turf. The working depth can be adjusted via spindles. The 1-cylinder petrol engine provides sufficient power to work very effectively with a width of 600 mm. A weight of 75 kg and a fold-away handle make it easy and extremely handy to transport the TP600.





TurfPickup TP600



1-cylinder petrol engine for the drive of the tine shaft



Working depth adjustable via spindles



Rotating shaft with flexible tines

Recommended accessories for TurfPickup TP600

Chassis	Laser-cut steel frame construction, plastic-coated
Drive	1-cylinder petrol engine 2.5 kW (3.4 HP)
Working width	600 mm
Working speed	10 m/min
Performance	360 m ² /h
Weight	75 kg
Dimension	L 800 x W 570 x H 960 mm

Subject to technical alterations




FloorTest FT50

Page 87



Gloves

Page 89




Hearing protector

Page 89



Safety glasses

Page 89



Dust mask

Page 89